DIELECTRIC RESONATOR OSCILLATOR

Model 515105

8000 - 9000 MHz

Features

- Low Noise
- Rugged Construction for Extreme Environmental Conditions
- High Frequency Stability
- Mechanically Tuned

Specifications

CHARACTERISTIC	TYPICAL Ta = +25 ºC	MIN/MAX Ta = -55ºC to +85 ºC
Frequency	8000 - 9000 MHz	8000 - 9000 MHz
Output Power (dBm)	+13.0	+10.0 Min.
Power Flatness (dBm)	+/- 1.5	+/- 3.0
Frequency Stability (ppm)/ ºC	4	3 to 5
Harmonics (dBc)	-20	-15 Max.
Spurious (dBc)	-80	-80 Max.
Phase Noise (8000 MHz) @ 100 KHz (dBc/Hz)	-124	-122 Max.
Load VSWR	1.5:1	2.0:1 Max.
Power Vdc	+15	+15 to +20
mA	70	90 Max.

Absolute Maximum (No Damage) Ratings

Ambient Operating Temperature ..... -55ºC to +100 ºC
Storage Temperature ..... -62ºC to +125 ºC
Case Temperature ..... +125 ºC
DC Voltage ..... +24 Volts
Maximum DC Tuning Voltage ..... +20 Volts
Minimum DC Tuning Voltage ..... 0 Volts

NOTE: Care should always be taken to effectively ground the case of each unit.

Typical Performance Data

Phase Noise Offset	Typical 8000 MHz	Typical 9000 MHz
1 kHz	-80	-77
10 kHz	-104	-103
100 kHz	-124	-123

Output Power



Phase Noise (dBc/Hz) 8000 MHz



Phase Noise (dBc/Hz) 9000 MHz



Mechanical Outline



Note
OSC. ADJ. Location approx. as shown

Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

Rev. 5/5/10

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001